



1500 RPM, 50 Hertz, 12 Lead, 4 Pole, 1 Phase, 40°C Ambient						Double Delta 220-240V
Model Number	CONTINUOUS DUTY					
	0.8 PF					
	Class F (105°C)		Class H (125°C)		Efficiency %	
	kVA	kW	kVA	kW		
AFD1112	4.4	3.5	4.7	3.8	72.6	
AFD2112	5.8	4.6	6.4	5.1	76.3	
AFD3112	7.3	5.8	7.8	6.2	77.8	
AFD4112	8.7	7.0	9.3	7.4	78.8	
AHD5112	11.6	9.3	13.0	10.4	82.1	
AHD6112	14.5	11.6	16.0	12.8	84.3	
AHD7112	16.8	13.4	18.1	14.5	85.0	
AHD8112	20.0	16.0	21.8	17.4	83.7	
AHD9112	22.5	18.0	23.3	18.6	84.2	
BBD3112	25.0	20.0	28.5	22.8	86.4	
BBD4112	30.0	24.0	33.5	26.8	87.2	
BBD5112	35.5	28.4	40.0	32.0	87.8	
BBD6112	43.5	34.8	48.5	38.8	89.3	
BBD7112	50.0	40.0	56.5	45.2	89.4	
BGD3112	50.0	40.0	60.0	48.0	90.2	
BGD4112	60.0	48.0	68.0	54.4	90.5	
BGD5112	75.0	60.0	85.0	68.0	91.4	
BGD6112	87.0	70.0	96.0	76.8	91.8	
BGD7112	96.0	77.0	105.0	84.0	92.1	
BGD8112	110.0	88.0	120.0	96.0	92.7	
DDD3112	110	88	125	100	91.9	
DDD4112	130	104	145	116	92.0	
DDD5112	150	120	160	140	92.5	
DDD6112	175	140	190	152	92.4	

