



TrophyMDI™
GENERATORS

1500 RPM, 50 Hertz, 12 Lead, 4 Pole, 3 Phase, 0.8 PF, 40°C Ambient								Series Star (Wye) 380-440V Parallel Star (Wye) 190-220V Series Delta 200-240V	
Model Number	CONTINUOUS DUTY							STANDBY DUTY	
	Class B (80°C)		Class F (105°C)		Class H (125°C)		Efficiency PF 0.8	Class H (150°C)	
	kVA	kW	kVA	kW	kVA	kW		kVA	kW
1B4S12-MDI-2812	8.0	6.4	10.0	8.0	11.0	8.8	80.5	N/A	N/A
1C4S12-MDI-2823	10.0	8.0	12.5	10.0	13.5	10.8	81.7	N/A	N/A
1D4S12-MDI-2824	12.0	9.6	15.0	12.0	16.0	12.8	82.7	N/A	N/A
2E4S12-MDI-2825	15.0	12.0	20.0	16.0	22.5	18.0	85.6	N/A	N/A
2F4S12-MDI-2826	20.0	16.0	25.0	20.0	27.5	22.0	86.7	29.0	23.0
2G4S12-MDI-2837	22.2	17.8	29.0	23.2	31.3	25.0	87.6	33.0	26.0
2H4S12-MDI-2848	29.2	23.4	34.4	27.5	37.5	30.0	87.5	39.0	31.0
2J4S12 -MDI-2842	31.5	25.2	39.0	31.2	40.0	32.0	87.8	44.0	35.0
3C4S12-MDI-3610	34.7	27.8	37.5	30.0	42.5	34.0	87.9	45.0	36.0
3E4S12 -MDI-3611	47.0	37.6	53.0	42.4	60.0	48.0	89.4	61.0	49.0
3F4S12-MDI-3612	56.4	45.1	65.0	52.0	72.5	58.0	90.5	77.0	61.0
3G4S12-MDI-3624	65.6	52.5	75.0	60.0	85.0	68.0	91.0	87.0	70.0
4C4S12-MDI-3626	76.1	60.9	83.8	67.0	100.0	80.0	91.0	106.0	84.0
4E4S12-MDI-3637	111.6	89.3	125.0	100.0	140.0	112.0	92.1	145.0	116.0
4F4S12-MDI-4312	130.0	104.0	145.0	116.0	160.0	128.0	92.6	170.0	136.0
4G4S12-MDI-4314	141.8	113.4	163.8	131.0	180.0	144.0	92.8	187.0	149.0
4H4S12-MDI-4316	164.7	131.8	181.3	145.0	200.0	160.0	93.6	212.0	169.0
4J4S12-MDI-4318	170.0	144.5	210.0	168.0	225.0	180.0	93.8	236.0	189.0
5D4S12-MDI-4322	221.0	177.0	268.0	214.0	300.0	240.0	93.5	345.0	376.0
5F4S12-MDI-4330	296.0	236.0	350.0	280.0	375.0	300.0	93.8	512.0	410.0



Manassas, VA 20110 - 804-493-1777 - www.athlongenerator.com