



TrophyMDI™
GENERATORS

**1500 RPM, 50 Hertz, 4 Lead, 4 Pole,
Dedicated 1 Phase, 40°C Ambient**

Series 220-240V
Parallel 110-120V

Model Number	CONTINUOUS DUTY								Efficiency %
	PF 0.8						PF 1.0		
	Class B (80°C)		Class F (105°C)		Class H (125°C)				
	kVA	kW	kVA	kW	kVA	kW	kW	kW	
1C4S04-MDI-2824	6.8	5.4	8.5	6.8	9.0	7.2	9.6	11.0	75.5
2E4S04-MDI-2826	10.8	8.6	13.5	10.8	15.0	12.0	15.0	16.6	81.9
2G4S04-MDI-2837	15.5	12.4	19.4	15.5	21.0	16.8	20.5	22.8	83.9
3D4S04 -MDI-3611	25.2	20.2	31.5	25.2	35.0	28.0	31.5	35.0	85.1
3E4S04-MDI-3612	28.8	23.0	36.0	28.8	40.0	32.0	36.0	40.0	86.1
3F4S04-MDI-3613	36.0	28.8	45.0	36.0	50.0	40.0	45.0	50.0	87.5
3G4S04-MDI-3625	43.2	34.6	54.0	43.2	60.0	48.0	54.0	60.0	88.3
4E4S04-MDI-4312	67.0	53.8	84.0	67.0	94.0	75.0	84.0	94.0	88.5
4G4S04-MDI-4314	86.0	69.0	108.0	86.0	120.0	96.0	108.0	120.0	89.6



Manassas, VA 20110 - 804-493-1777 - www.athlongenerator.com