



TrophyMDI™
GENERATORS

1800 RPM, 60 Hertz, 12 Lead, 4 Pole, 1 Phase, 0.8 PF, 40°C Ambient					Double Delta 200-240V
Model Number	CONTINUOUS DUTY				Efficiency %
	Class F (105°C)		Class H (125°C)		
		kW, 0.8 PF	kW, 1.0 PF	kW, 0.8 PF	
1B4S12-MDI-2812	6.9	5.5	8.5	6.0	75.7
1C4S12-MDI-2823	8.6	6.9	10.5	7.4	77.1
1D4S12-MDI-2824	10.3	8.3	12.5	8.8	78.2
2E4S12-MDI-2825	14.5	11.6	18.0	12.8	80.6
2F4S12-MDI-2826	17.5	14.0	21.5	15.0	83.2
2G4S12-MDI-2837	18.1	14.5	23.0	16.2	84.6
2H4S12-MDI-2848	26.6	18.9	29.0	20.6	83.7
2J4S12-MDI-2842	28.3	20.0	31.0	21.9	84.3
3C4S12-MDI-3610	30.0	24.0	33.5	26.8	81.8
3E4S12-MDI-3611	42.0	33.5	45.0	36.0	85.4
3F4S12-MDI-3612	50.0	40.0	56.0	45.0	86.9
3G4S12-MDI-3624	58.8	47.0	62.5	50.0	87.3
4C4S12-MDI-3626	60.0	48.0	67.5	54.0	86.3
4E4S12-MDI-3637	84.0	67.2	96.0	76.8	88.8
4F4S12-MDI-4312	97.5	78.0	108.8	87.0	89.6
4G4S12-MDI-4314	115.0	92.3	123.4	98.7	89.7
4H4S12-MDI-4316	131.3	105.0	142.5	114.0	90.7
5D4S12-MDI-4322	160.0	128.0	170.0	136.0	92.2
5F4S12-MDI-4330	210.0	168.0	230.0	184.0	92.8



Manassas, VA 20110 - 804-493-1777 - www.athlongenerator.com