



1800 RPM, 60 Hertz, 12 Lead, 4 Pole, 1 Phase, 40°C Ambient						Double Delta 200-240V
Model Number	CONTINUOUS DUTY					
	0.8 PF					
	Class F (105°C)		Class H (125°C)		Efficiency %	
	kVA	kW	kVA	kW		
AFD1112	5.2	4.1	6.5	4.5	71.9	
AFD2112	6.9	5.5	8.5	6.0	75.7	
AFD3112	8.6	6.9	10.5	7.4	77.1	
AFD4112	10.3	8.3	12.5	8.8	78.2	
AHD5112	14.5	11.6	18.0	12.8	80.6	
AHD6112	17.5	14.0	21.5	15.0	83.2	
AHD7112	18.1	14.5	23.0	16.2	84.6	
AHD8112	26.6	18.9	29.0	20.6	83.7	
AHD9112	28.3	20.0	31.0	21.9	84.3	
BBD3112	30.0	24.0	33.5	26.8	81.8	
BBD4112	35.0	28.0	40.0	32.0	84.2	
BBD5112	42.0	33.5	45.0	36.0	85.4	
BBD6112	50.0	40.0	56.0	45.0	86.9	
BBD7112	58.8	47.0	62.5	50.0	87.3	
BGD3112	60.0	48.0	67.5	54.0	86.3	
BGD4112	72.0	57.6	78.8	63.0	87.3	
BGD5112	84.0	67.2	96.0	76.8	88.8	
BGD6112	97.5	78.0	108.8	87.0	89.6	
BGD7112	115.0	92.3	123.4	98.7	89.7	
BGD8112	131.3	105.0	142.5	114.0	90.7	
DDD3112	130	104	140	112	91.8	
DDD4112	160	128	170	136	92.2	
DDD5112	185	148	200	160	92.8	
DDD6112	210	168	230	184	92.8	

