



**1800 RPM, 60 Hertz, 12 Lead, 4 Pole,
3 Phase, 0.8 PF, 40°C Ambient**

Series Star (Wye) 380-480V
Parallel Star (Wye) 190-240V
Series Delta 240-277V

Model Number	CONTINUOUS DUTY							STANDBY DUTY	
	Class B (80°C)		Class F (105°C)		Class H (125°C)		Efficiency PF 0.8	Class H (150°C)	
	kVA	kW	kVA	kW	kVA	kW		kVA	kW
1B4S12-MDI-2812	11.0	8.8	12.5	10.0	13.8	11.0	80.5	N/A	N/A
1C4S12-MDI-2823	13.5	10.8	15.6	12.5	16.9	13.5	81.7	N/A	N/A
1D4S12-MDI-2824	16.0	12.8	18.8	15.0	20.0	16.0	82.7	N/A	N/A
2E4S12-MDI-2825	19.7	15.8	26.3	21.0	28.8	23.0	85.6	N/A	N/A
2F4S12-MDI-2826	25.8	20.6	31.3	25.0	34.4	27.5	86.7	35.0	28.0
2G4S12-MDI-2837	28.3	22.7	34.4	27.5	37.5	30.0	87.6	38.8	31.0
2H4S12-MDI-2848	37.5	30.0	43.0	34.4	46.9	37.5	87.5	48.5	38.8
2J4S12-MDI-2842	40.0	32.0	45.8	36.6	50.0	40.0	87.8	52.0	41.6
3C4S12-MDI-3610	43.6	34.8	46.3	37.0	52.5	42.0	87.9	55.0	44.0
3E4S12-MDI-3611	60.0	48.2	65.0	52.0	70.0	56.0	89.4	73.0	59.0
3F4S12-MDI-3612	72.0	58.1	78.0	62.0	87.5	70.0	90.5	92.0	74.0
3G4S12-MDI-3624	84.0	67.0	93.0	75.0	100.0	80.0	91.0	102.0	82.0
4C4S12-MDI-3626	96.0	77.0	106.0	85.0	117.5	94.0	91.0	125.0	100.0
4E4S12-MDI-3637	138.0	110.0	143.0	115.0	168.0	134.0	92.1	175.0	140.0
4F4S12-MDI-4312	165.0	132.0	172.0	138.0	190.0	152.0	92.6	200.0	160.0
4G4S12-MDI-4314	188.0	150.0	199.0	159.0	213.0	170.0	92.8	228.0	183.0
4H4S12-MDI-4316	209.3	167.4	225.0	180.0	245.0	196.0	93.6	258.0	207.0
4J4S12-MDI-4318	230.0	183.8	247.0	198.0	281.0	225.0	93.8	295.0	236.0
5D4S12-MDI-4322	298.0	239.0	330.0	264.0	360.0	288.0	93.5	388.0	310.0
5F4S12-MDI-4330	399.0	319.0	425.0	340.0	463.0	370.0	93.8	488.0	390.0

