



**TrophyMDI™**  
GENERATORS

1800 RPM, 60 Hertz, 4 Lead, 4 Pole, Dedicated 1 Phase, 40°C Ambient									Series 220-240V Parallel 110-120V
Model Number	CONTINUOUS DUTY								Efficiency %
	PF 0.8						PF 1.0		
	Class B (80°C)		Class F (105°C)		Class H (125°C)		kW	kW	
	kVA	kW	kVA	kW	kVA	kW	kW	kW	
1C4S04 -MDI-2824	8.0	6.4	10.0	8.0	10.8	8.6	12.4	13.5	75.8
2E4S04 -MDI-2826	13.2	10.6	16.5	13.2	18.4	14.7	19.0	21.0	82.0
2G4S04 -MDI-2837	18.4	14.7	23.0	18.4	25.0	20.0	27.0	30.8	84.2
2H4S04 -MDI-2848	23.0	18.4	28.7	23.0	31.3	25.0	32.0	35.0	84.5
2J4S04 -MDI-2840	25.6	20.5	32.0	25.6	35.0	28.0	36.0	40.0	84.6
3D4S04 -MDI-3611	32.0	25.6	40.0	32.0	44.0	35.0	40.0	44.0	84.8
3E4S04 -MDI-3612	37.8	30.2	47.3	37.8	50.0	40.0	47.3	50.0	85.5
3F4S04 -MDI-3613	45.5	36.4	56.9	45.5	60.0	48.0	56.9	60.0	86.3
3G4S04 -MDI-3625	52.5	42.0	65.0	52.5	70.0	56.0	65.6	75.0	87.5
4D4S04-MDI-3637	70.0	56.0	87.5	70.0	96.0	77.0	87.0	100.0	87.8
4E4S04-MDI-4312	80.0	64.0	100.0	80.0	112.0	90.0	100.0	115.0	87.9
4G4S04-MDI-4314	110.0	88.0	137.5	110.0	150.0	120.0	137.0	150.0	89.2
4H4S04-MDI-4316	115.0	92.0	143.8	115.0	156.0	125.0	143.0	156.0	90.1



Manassas, VA 20110 - 804-493-1777 - [www.athlongenerator.com](http://www.athlongenerator.com)