



**1800 RPM, 60 Hertz, 4 Lead, 4 Pole,
Dedicated 1 Phase, 40°C Ambient**

Series 220-240V
Parallel 110-120V

Model Number	CONTINUOUS DUTY								Efficiency %
	PF 0.8				PF 1.0				
	Class B (80°C)		Class F (105°C)		Class H (125°C)		105°C	125°C	
	kVA	kW	kVA	kW	kVA	kW	kW	kW	
AFD1104	4.7	3.8	5.9	4.7	6.4	5.1	7.5	8.2	70.5
AFD2104	6.4	5.1	8.0	6.4	8.8	7.0	10.0	11.0	74.1
AFD3104	8.0	6.4	10.0	8.0	10.8	8.6	12.4	13.5	75.8
AFD4104	9.8	7.8	12.3	9.8	13.5	10.8	15.0	16.5	77.0
AHD5104	13.2	10.6	16.5	13.2	18.4	14.7	19.0	21.0	82.0
AHD6104	16.0	12.8	20.0	16.0	21.9	17.5	23.0	25.6	83.5
AHD7104	18.4	14.7	23.0	18.4	25.0	20.0	27.0	30.8	84.2
AHD8104	23.0	18.4	28.7	23.0	31.3	25.0	32.0	35.0	84.5
AHD9104	25.6	20.5	32.0	25.6	35.0	28.0	36.0	40.0	84.6
BBD3104	27.0	21.6	33.8	27.0	37.5	30.0	33.8	37.5	84.8
BBD4104	32.0	25.6	40.0	32.0	44.0	35.0	40.0	44.0	85.5
BBD5104	37.8	30.2	47.3	37.8	50.0	40.0	47.3	50.0	86.3
BBD6104	45.5	36.4	56.9	45.5	60.0	48.0	56.9	60.0	87.5
BBD7104	52.5	42.0	65.0	52.5	70.0	56.0	65.6	75.0	88.4
BGD3104	60.0	48.0	75.0	60.0	84.0	67.0	75.0	90.0	87.8
BGD4104	70.0	56.0	87.5	70.0	96.0	77.0	87.0	100.0	87.9
BGD5104	80.0	64.0	100.0	80.0	112.0	90.0	100.0	115.0	88.9
BGD6104	100.0	80.0	125.0	100.0	135.0	108.0	125.0	135.0	89.2
BGD7104	110.0	88.0	137.5	110.0	150.0	120.0	137.0	150.0	90.1
BGD8104	115.0	92.0	143.8	115.0	156.0	125.0	143.0	156.0	90.8

