



1500 RPM, 50 Hertz, 12 Lead, 4 Pole, 3 Phase, 0.8 PF, 40°C Ambient								Series Star (Wye) 380-440V	Parallel Star (Wye) 190-240V	Series Delta 200-240V
Model Number	CONTINUOUS DUTY							STANDBY DUTY		
	Class B (80°C)		Class F (105°C)		Class H (125°C)		Efficiency PF 0.8	Class H (150°C)		
	kVA	kW	kVA	kW	kVA	kW		kVA	kW	
AFD1112	6.4	5.1	7.5	6.0	8.1	6.5	77.4	N/A	N/A	
AFD2112	8.0	6.4	10.0	8.0	11.0	8.8	80.5	N/A	N/A	
AFD3112	10.0	8.0	12.5	10.0	13.5	10.8	81.7	N/A	N/A	
AFD4112	12.0	9.6	15.0	12.0	16.0	12.8	82.7	N/A	N/A	
AHD5112	15.0	12.0	20.0	16.0	22.5	18.0	85.6	N/A	N/A	
AHD6112	20.0	16.0	25.0	20.0	27.5	22.0	86.7	29	23	
AHD7112	22.2	17.8	29.0	23.2	31.3	25.0	87.6	33	26	
AHD8112	29.2	23.4	34.4	27.5	37.5	30.0	87.5	39	31	
AHD9112	31.5	25.2	39.0	31.2	40.0	32.0	87.8	44	35	
BBD3112	34.7	27.8	37.5	30.0	42.5	34.0	87.9	45	36	
BBD4112	40.7	32.6	45.0	36.0	50.0	40.0	88.8	53	42	
BBD5112	47.0	37.6	53.0	42.4	60.0	48.0	89.4	61	49	
BBD6112	56.4	45.1	65.0	52.0	72.5	58.0	90.5	77	61	
BBD7112	65.6	52.5	75.0	60.0	85.0	68.0	91.0	87	70	
BGD3112	76.1	60.9	83.8	67.0	100.0	80.0	91.0	106	84	
BGD4112	88.6	70.9	105.0	84.0	125.0	100.0	91.2	127	101	
BGD5112	111.6	89.3	125.0	100.0	140.0	112.0	92.1	145	116	
BGD6112	130.0	104.0	145.0	116.0	160.0	128.0	92.6	170	136	
BGD7112	141.8	113.4	163.8	131.0	180.0	144.0	92.8	187	149	
BGD8112	164.7	131.8	181.3	145.0	200.0	160.0	93.6	212	169	
BGD9112	170.0	144.5	210.0	168.0	225.0	180.0	93.8	236	189	
BGD10112	185.0	148.0	216.3	173.0	250.0	200.0	93.0	250	200	
DDD3112	197	158	220	176	250	200	92.8	313	250	
DDD4112	221	177	268	214	300	240	93.5	345	376	
DDD5112	267	213	300	240	325	260	93.6	390	312	
DDD6112	296	236	350	280	375	300	93.8	512	410	
EDD3112	365	292	445	356	450	360	94.0	575	460	
EDD4112	410	328	495	396	500	400	94.4	640	512	
EDD5112	483	386	560	448	600	480	94.9	710	568	
EDD6112	517	414	620	496	670	536	94.9	800	640	
FDD2112	587	469	690	552	750	600	93.3	848	678	
FDD3112	627	502	738	590	800	640	93.6	965	772	
FDD4112	714	672	840	672	910	728	93.5	1060	848	
FDD5112	786	629	925	740	1000	800	94.3	1200	960	
FDD6112	888	755	1045	836	1130	904	94.8	1325	1060	
FDD7112	982	785	1155	924	1250	1000	95.0	1550	1240	
GDD2112	N/A	N/A	1280	1024	1375	1100	95.6	1430	1144	
GDD3112	N/A	N/A	1415	1132	1520	1216	96.0	1590	1272	
GDD4112	N/A	N/A	1505	1204	1620	1296	96.4	1685	1348	
GDD5112	N/A	N/A	1735	1388	1865	1492	96.3	1940	1552	
GDD6112	N/A	N/A	1880	1504	2040	1632	96.6	2125	1700	
GDD7112	N/A	N/A	2005	1604	2160	1728	96.3	2250	1800	

