



1800 RPM, 60 Hertz, 12 Lead, 4 Pole, 3 Phase, 0.8 PF, 40°C Ambient								Series Star (Wye) 416-480V Parallel Star (Wye) 208-240V Series Delta 240-277V	
Model Number	CONTINUOUS DUTY						STANDBY DUTY		
	Class B (80° C)		Class F (105° C)		Class H (125° C)		Efficiency PF 0.8	Class H (150° C)	
	kVA	kW	kVA	kW	kVA	kW		kVA	kW
AFD1112	8.2	6.6	9.4	7.5	10.2	8.2	77.4	N/A	N/A
AFD2112	11.0	8.8	12.5	10.0	13.8	11.0	80.5	N/A	N/A
AFD3112	13.5	10.8	15.6	12.5	16.9	13.5	81.7	N/A	N/A
AFD4112	16.0	12.8	18.8	15.0	20.0	16.0	82.7	N/A	N/A
AHD5112	19.7	15.8	26.3	21.0	28.8	23.0	85.6	N/A	N/A
AHD6112	25.8	20.6	31.3	25.0	34.4	27.5	86.7	35	28
AHD7112	28.3	22.7	34.4	27.5	37.5	30.0	87.6	39	31
AHD8112	37.5	30.0	43.0	34.4	46.9	37.5	87.5	48	38
AHD9112	40.0	32.0	45.8	36.6	50.0	40.0	87.8	52	41
BBD3112	43.6	34.8	46.3	37.0	52.5	42.0	87.9	55	44
BBD4112	52.7	42.2	56.0	44.8	62.5	50.0	88.8	65	52
BBD5112	60.0	48.2	65.0	52.0	70.0	56.0	89.4	73	59
BBD6112	72.0	58.1	78.0	62.0	87.5	70.0	90.5	92	74
BBD7112	84.0	67.0	93.0	75.0	100.0	80.0	91.0	102	82
BGD3112	96.0	77.0	106.0	85.0	117.5	94.0	91.0	125	100
BGD4112	110.0	88.0	125.0	100.0	150.0	120.0	91.2	145	116
BGD5112	138.0	110.0	143.0	115.0	168.0	134.4	92.1	175	140
BGD6112	165.0	132.0	172.0	138.0	190.0	152.0	92.6	200	160
BGD7112	188.0	150.0	199.0	159.0	213.0	170.0	92.8	228	183
BGD8112	209.3	167.4	225.0	180.0	245.0	196.0	93.6	258	207
BGD9112	230.0	183.8	247.0	198.0	281.0	225.0	93.8	295	236
BGD10112	257.0	206.0	275.0	220.0	300.0	240.0	94.1	312	250
DDD3112	257	206	275	220	300	240	92.8	320	256
DDD4112	298	239	330	264	360	288	93.5	388	310
DDD5112	350	280	375	300	400	320	93.6	431	345
DDD6112	399	319	425	340	463	370	93.8	488	390
EDD3112	487	389	531	425	581	465	94.0	613	490
EDD4112	538	430	563	450	625	500	94.4	655	524
EDD5112	613	491	663	530	732	586	94.9	780	624
EDD6112	673	538	731	585	800	640	94.9	848	678
FDD2112	718	575	823	659	895	716	93.3	942	754
FDD3112	766	613	880	704	958	766	93.6	1010	808
FDD4112	875	700	1000	800	1090	872	93.5	1150	920
FDD5112	958	766	1100	880	1197	958	94.3	1280	1024
FDD6112	1066	852	1225	980	1332	1066	94.8	1400	1120
FDD7112	1160	928	1340	1072	1449	1159	95.0	1550	1240
GDD2112	N/A	N/A	1540	1232	1655	1324	95.6	1725	1380
GDD3112	N/A	N/A	1725	1380	1855	1484	95.8	1930	1544
GDD4112	N/A	N/A	1840	1472	1975	1580	96.3	2055	1644
GDD5112	N/A	N/A	2100	1680	2250	1800	96.2	2345	1876
GDD6112	N/A	N/A	2370	1896	2550	2040	96.4	2600	2080
GDD7112	N/A	N/A	2445	1956	2625	2100	96.3	2725	2180

