



	3600 RPM, 60 Hertz, 2 Pole, 40°C Ambient, Class H (125°C)			3000 RPM, 50 Hertz, 2 Pole, 40°C Ambient, Class H (125°C)		
Model Number	3 Phase, 0.8 PF, 12 Leads Series Star (Wye) 380-480V Parallel Star (Wye) 190-240V			3 Phase, 0.8 PF, 12 Leads Series Star (Wye) 380-440V Parallel Star (Wye) 190-220V		
	KVA	kW	Efficiency	KVA	kW	Efficiency
AFB1112	15.6	12.5	73.5	12.5	10.0	74.0
AFB2112	18.8	15.0	77.0	15.0	12.0	77.5
AFB3112	21.9	17.5	79.2	17.5	14.0	79.6
AFB4112	31.3	25.0	81.7	25.0	20.0	81.9
AHB8112	35.0	28.0	82.0	30.0	24.0	82.3
AHB9112	40.0	32.0	83.1	35.0	28.0	83.4
AHB10112	46.9	37.5	84.4	37.5	30.0	85.0
Model Number	1 Phase, 0.8 PF, 4 Leads Series 220-240V Parallel 110-120V			1 Phase, 0.8 PF, 4 Leads Series 220-240V Parallel 110-120V		
	KVA	kW	Efficiency	KVA	kW	Efficiency
AFB1104	10.0	8.0	65.3	8.4	6.7	68.4
AFB2104	12.4	9.9	70.1	10.0	8.0	72.0
AFB3104	14.4	11.5	72.6	11.8	9.4	74.3
AFB4104	20.6	16.5	75.9	16.8	13.4	77.4
AHB8104	24.8	19.8	76.2	20.0	16.0	77.9
AHB9104	28.9	23.1	77.6	23.5	18.8	79.3
AHB10104	31.0	24.8	79.2	25.0	20.0	80.8

