



Locked Rotor Ratings							
1 Phase, 50/60 Hz, 4 Lead, 4 Pole, 0.8 PF, 40° C Ambient							
Classic Plus Model Number	Trophy MDI Model Number	Locked Rotor KVA, $\leq 30\%$ Transient Voltage Dip					
		Non-PMG			PMG		
		220V	230V	240V	220V	230V	240V
AFD1104	N/A	10.6	11.6	12.6	Not Available as PMG		
AFD2104	N/A	14.6	16.0	17.5			
AFD3104	1C4S04-MDI-2823	16.4	17.9	19.5			
AFD4104	N/A	21.0	22.8	24.7			
AHD5104	2E4S04-MDI-2825	30.7	33.5	36.5			
AHD6104	N/A	36.4	40.0	43.0			
AHD7104	2G4S04-MDI-2837	42.0	45.0	49.0			
AHD8104	2H4S04-MDI-2848	46.0	50.0	55.0			
AHD9104	2J4S04-MDI-2842	53.0	58.0	63.0			
BBD3104	N/A	67.0	73.0	80.0	77	83	91
BBD4104	3D4S04-MDI-3611	74.0	81.0	88.0	95	105	115
BBD5104	3E4S04-MDI-3612	78.0	85.0	93.0	103	113	122
BBD6104	3F4S04-MDI-3613	112	122	133	142	155	169
BBD7104	3G4S04-MDI-3625	142	156	170	169	184	202
BGD3104	N/A	177	194	210	223	245	265
BGD4104	4D4S04-MDI-3637	225	247	270	292	319	348
BGD5104	4E4S04-MDI-4312	243	264	289	301	330	357
BGD6104	N/A	273	300	325	352	385	418
BGD7104	4G4S04-MDI-4314	330	363	394	430	472	513
BGD8104	4H4S04-MDI-4316	336	367	400	470	515	568