



Locked Rotor Ratings, Non-PMG						
3 Phase, 50 Hz, 12 Lead, 4 Pole, 0.8 PF, 40°C Ambient						
Classic Plus Model Number	Classic Plus Marine Model Number	Trophy MDI Model Number	Locked Rotor KVA, $\leq 30\%$ Transient Voltage Dip			
			50Hz			
			380V	400V	415V	440V
AFD1112	N/A	N/A	13.2	14.6	15.8	17.8
AFD2112	N/A	1B4S12-MDI-2812	17.0	18.6	20.3	22.7
AFD3112	N/A	1C4S12-MDI-2823	20.1	22.3	23.9	26.8
AFD4112	N/A	1D4S12-MDI-2824	23.7	26.4	28.3	31.8
AHD5112	N/A	2E4S12-MDI-2825	32.9	36.4	39.2	44.0
AHD6112	N/A	2F4S12-MDI-2826	41.0	45.3	48.7	54.6
AHD7112	N/A	2G4S12-MDI-2837	47.5	52.4	56.8	63.6
AHD8112	N/A	2H4S12-MDI-2848	59.7	66.8	70.9	79.9
AHD9112	N/A	2J4S12-MDI-2842	65.8	72.9	78.3	88.2
BBD3112	BBD3112M	3C4S12-MDI-3610	65.8	82.8	93.1	103.5
BBD4112	BBD4112M	N/A	80.7	100.0	115.1	124.5
BBD5112	BBD5112M	3E4S12-MDI-3611	98.6	117.0	134.8	151.0
BBD6112	BBD6112M	3F4S12-MDI-3612	112.3	147.5	167.2	191.0
BBD7112	BBD7112M	3G4S12-MDI-3624	148	177	202	240
BGD3112	BGD3112M	4C4S12-MDI-3626	184	225	255	N/A
BGD4112	BGD4112M	N/A	210	257	291	N/A
BGD5112	BGD5112M	4E4S12-MDI-3637	270	324	380	N/A
BGD6112	BGD6112M	4F4S12-MDI-4312	294	352	387	N/A
BGD7112	BGD7112M	4G4S12-MDI-4314	346	428	491	N/A
BGD8112	BGD8112M	4H4S12-MDI-4316	396	463	527	N/A
BGD9112	N/A	4J4S12-MDI-4318	445	493	529	N/A
BGD10112	N/A	N/A	508	564	605	N/A
DDD3112	DDD3112M	N/A	428	499	534	668
DDD4112	DDD4112M	5D4S12-MDI-4322	470	510	573	710
DDD5112	DDD5112M	N/A	529	639	714	897
DDD6112	DDD6112M	5F4S12-MDI-4330	621	739	814	993
EDD3112	EDD3112M	N/A	734	830	940	1175
EDD4112	EDD4112M	N/A	856	950	1070	1338
EDD5112	EDD5112M	N/A	953	1087	1285	1565
EDD6112	EDD6112M	N/A	1046	1193	1369	1649
FDD2112	FDD2112M	N/A	Only Available as PMG			
FDD3112	FDD3112M	N/A				
FDD4112	FDD4112M	N/A				
FDD5112	FDD5112M	N/A				
FDD6112	FDD6112M	N/A				
FDD7112	FDD7112M	N/A				
GDD2112	GDD2112M	N/A	Only Available as PMG			
GDD3112	GDD3112M	N/A				
GDD4112	GDD4112M	N/A				
GDD5112	GDD5112M	N/A				
GDD6112	GDD6112M	N/A				
GDD7112	GDD7112M	N/A				